

teXXmo *your ticket to mobility!*

KALEO DT313C



teXXmo

Mobile Solution
GmbH & Co. KG
Otto-Lilienthal-Str. 36
D-71034 Böblingen

fon +49 70 31-71 48 50
fax +49 70 31-71 48 49

www.teXXmo.com
info@teXXmo.com

KALEO DT313C

System - System	
CPU <i>Prozessor</i>	Intel® Celeron®, 1.4GHz
RAM <i>Arbeitsspeicher</i>	4GB
Storage <i>Festplattenkapazität</i>	64GB to 512GB
Operating System <i>Betriebssystem</i>	Microsoft® Windows® 7 Pro, Windows® 10 IoT Enterprise; 64bit, Android 8.0
Display <i>Bildschirm</i>	33,8 cm (13.3") LED-backlight screen with capacitive touch
Display Resolution <i>Bildschirmauflösung</i>	1920 x 1080 (HD)
Network <i>Netzwerk</i>	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band; Bluetooth 4.0 LE
Trusted Platform Module <i>Trusted Platform Module</i>	TPM 1.2 support
Control Switch and Button <i>Tasten</i>	1 power button, 1 programmable button and 1 Wi-Fi switch
Indicator <i>Anzeigen</i>	1 power/ battery status LED
Speaker, Microphone <i>Lautsprecher, Mikrofon</i>	built-in speaker, Microphone with DSP for video conference call
Fan <i>Lüfter</i>	Fan
SD Slot <i>SD-Kartenleser</i>	1 full size SD card slot
I/O Ports - Anschlüsse	
USB 3.0 Port <i>USB 2.0 Anschluss</i>	1
Audio Port <i>Audio-Anschluß</i>	2
Power-in <i>Stromanschluß</i>	1
Smart Card Reader <i>Smart Card Kartenlese</i>	Full-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card
Mechanical and Environmental - Umgebung	
AC/DC Adapter <i>Netzteil</i>	Input: 100 – 240V AC; Output: 19V DC, 3.42A
Battery Pack <i>Akkupack</i>	Internal 14.8V, 1880mAh/ Optional: External 14.8V, 1850mAh
Enclosure <i>Gehäuse</i>	ABS + PC plastics
Stylus <i>Stift</i>	Yes, capacitive touch stylus (optional)
Protective Grips <i>Schutzecken</i>	Rubber bumpers on each corner for handling protection
Dimensions (H x W x D) <i>Abmessungen (H x B x T)</i>	216 x 344 x 18.9mm
Weight <i>Gewicht</i>	1.43 kg
Water and Dust Resistance <i>Schutz gegen Nässe u. Staub</i>	IP54 front panel
Shock and Vibration <i>Schock und Vibration</i>	MIL-STD-810G
Regulatory <i>Zertifizierungen</i>	FCC Class B, CE, RoHS compliant
Temperature <i>Temperatur</i>	Operation : 0°C – 40°C; Storage: -20°C – 60°C
Humidity <i>Luftfeuchtigkeit</i>	0% – 90% non-condensing
Options - Optionen	
Camera <i>Kamera</i>	2 megapixel front camera and 5 megapixel back camera
Barcode Scanner (2D) <i>Barcode Scanner (2D)</i>	2D barcode scanner; reads 1D also
Mobile broadband <i>Mobiles Breitband</i>	3G WWAN module or 4G LTE/AWS module



Desktop Charging Cradle



Wall/Vehicle Cradle



Battery



Battery Charger



X-Hand Strap



Shoulder Strap



Stylus



DC/DC-Adapter



Protective Foils

teXXmo

Mobile Solution
GmbH & Co. KG
Otto-Lilienthal-Str. 36
D-71034 Böblingen

fon +49 70 31-71 48 50
fax +49 70 31-71 48 49

www.teXXmo.com
info@teXXmo.com