

The Product

Introducing the new and powerful PORTEO-M, a compact and feature-packed thin client. The PORTEO-M small form factor offers space-savings in areas where users currently have large form factor devices connecting to various network classifications. The PORTEO-M has both USB and PS2 ports for government agencies that need to use multiple PORTEO-M devices with an approved KVM switch. The hidden parallel port is available for legacy printer devices when necessary. The uniquely-designed removable foot stand gives the PORTEO-M the flexible choice of either a vertical or horizontal profile. The PORTEO-M is also equipped with a mounting kit that supports standard VESA-mount and can be mounted on the back of a monitor to provide zero footprint on the desktop, essentially giving it an all-in-one feel. If you are looking for a powerful yet compact, small footprint thin-client with versatile I/O support, the PORTEO-M is the optimal choice.



Key Features

- ◆ Compact Thin Client Design
- ◆ Small Form Factor Offers Space Saving Advantage
- ◆ VIA® Eden V4, 1 GHz CPU
- ◆ VIA® CN700 and VT8237R+ Chipset
- ◆ 128 MB - 1 GB DDR2 SO-DIMM
- ◆ Maximum 8 GB Flash Storage Memory
- ◆ Integrated AGP AX Graphics
- ◆ 16 Bit Stereo FM Audio
- ◆ Four High-Speed USB 2.0 Ports (2 Front, 2 Rear)
- ◆ Support for Windows XPe, CE 6.0 and Linux
- ◆ Wireless Option
- ◆ VESA-Mount Option
- ◆ CE/UL/FCC Compliant



Mobile Solution
GmbH & Co. KG
Otto-Lilienthal-Str. 36
D-71034 Böblingen

fon +49 70 31-71 48 50
fax +49 70 31-71 48 49

www.teXXmo.com
info@teXXmo.com

Specifications

Processor	VIA® Eden V4 CPU 1 GHz (fanless cooling design)
System Memory	128 MB - 1 GB (single slot)
Flash Storage	128 MB - 8 GB (integrated)
Operating Systems	Windows® XP Embedded
Integrated Audio	AC97 2.0 Codec Compatible
Integrated LAN	10/100 Mbps, 1x RJ-45, optional internal USB 802.11 b/g WLAN
Integrated Video	CN700 with integrated AGP 8x Graphics Core, Shared System Memory 8 MB to 64 MB, Supports Resolutions of up to: 1600x1200 16-bit high color, 60 Hz
Integrated I/O	1x PS/2 Keyboard Port and 1x PS/2 Mouse Port, 4x USB 2.0 ports (2 at front, 2 at back), 1x Serial Port and One Parallel Port
Dimensions (H x W x D)	190 x 140 x 40 (mm)
Base Weight	700 g
Operating Temp.	5° - 40° C
Storage Temp.	-40° - 60° C
Humidity	10% - 90% non-condensing RH
Regulatory	FCC Declaration of Conformity (DoC) Underwriter Laboratories (UL) 60950, 3rd Edition CE



Applications

- ◆ Control and Monitoring
- ◆ Entertainment and Gaming
- ◆ Retail
- ◆ Inventory and Warehousing
- ◆ Education
- ◆ Hospitality
- ◆ Manufacturing
- ◆ Healthcare
- ◆ Finance